

# FC AUTOTROL

## SERIES ACTIVE CARBON SYSTEMS



### Standard Features

- Corrosion resistant FRP (Fiber wounded) body
- Programmable automatic AUTOTROL valf
- Automatic backwash time setler
- 3-6 Bar operating perssure
- Max. 10 bar test pressure
- Max. 50 C operating temperature
- Food grade Active Carbon mineral
- Electricity supply 220 V/50 Hz

### Advantages

- Easy to operate without any need full time operator
- Low operating cost
- Low energy cost

### Technical Features

CODE	MODEL	CONNECTION inc	FLOW m3/h		BACK WASH 20 m/h	TANK inc	TANK m2	MEDIA		TOTAL kg
			20 m/h	30 m/h				Gravel kg	A.Carbon kg	
MM.AFC20.1T	FC 20-1	1	0.6	0.9	0.6	8X35	0.03	3	10	29
MM.AFC30.1T	FC 30-1	1	1.0	1.5	1.0	10X35	0.05	5	15	36
MM.AFC50.1T	FC 50-1	1	1.0	1.5	1.0	10X54	0.05	5	20	44
MM.AFC70.11/4T	FC 70-1 1/4	1 1/4	1.8	2.7	1.8	13X54	0.09	15	35	75
MM.AFC100.11/4T	FC 100-1 1/4	1 1/4	2.0	3.0	2.0	14X65	0.10	20	50	103
MM.AFC125.11/4T	FC 125-1 1/4	1 1/4	2.6	3.9	2.6	16X65	0.13	20	60	114
MM.AFC150.11/4T	FC 150-1 1/4	1 1/4	3.2	4.8	3.2	18X65	0.16	25	75	149
MM.AFC150.2T	FC 150-2	2	3.2	4.8	4.4	18X65	0.16	25	100	177
MM.AFC200.2T	FC 200-2	2	4.4	6.6	5.8	21X62	0.22	50	120	259
MM.AFC250.2T	FC 250-2	2	5.8	8.7	9.0	24X72	0.29	75	200	401
MM.AFC400.2T	FC 400-2	2	9.0	13.5	13.2	30X72	0.45	100	300	558
MM.AFC600.2T	FC 600-2	2	13.2	19.8	17.8	36X72	0.66	150	350	750