

# TC-TCV AUTOTROL

## SERIES CABINET SOFTENING SYSTEMS



### Standard Features

- Corrosion resistant FRP (Fiber wounded) body
- Polyester cover on top of the cabinet
- Cabinet material HDPE (high density PE)
- Programmable automatic FLECK valf
- Time or flow controlled
- Automatic backwash time setter
- 3-6 Bar operating perssure
- Max. 10 bar test pressure
- Max. 50 C operating temperature
- Food grade resin mineral
- Electricity supply 220 V/50 Hz

### Advantages

- Easy to operate without any need full time operator
- Low operating cost
- Low energy cost
- Min. area requirement

### Technical Features

CODE	MODEL	CONNECTION inc	MAX.Flow m3/h	CAPACITY m3F	MEDIA Resin lt	TANK inc	SALT TANK cm	SALT CON. kg/reg	TOTAL kg
MM.ATC10.1T	TC 10-1	3/4 - 1	1.2	60	10	8X17	50X32X67	2	25
MM.ATC20.1T	TC 20-1	3/4 - 1	1.2	120	20	8X35	50X32X114	4	39
MM.ATC30.1T	TC 30-1	3/4 - 1	2.0	180	30	10X35	50X32X114	6	52
MM.ATC10.1V	TC 10-1V	3/4 - 1	1.2	60	10	8X17	50X32X67	2	25
MM.ATC20.1V	TC 20-1V	3/4 - 1	1.2	120	20	8X35	50X32X114	4	39
MM.ATC30.1V	TC 30-1V	3/4 - 1	2.0	180	30	10X35	50X32X114	6	52