

# TF AUTOTROL

## SERIES SOFTENING SYSTEMS



### Standard Features

- Corrosion resistant FRP (Fiber wounded) body
- Protection cover on top salt tank
- Programmable automatic FLECK valf
- Time controlled
- Automatic backwash time setler
- 3-6 Bar operating perssure
- Max. 10 bar test pressure
- Max. 50 C operating temperature
- Food grade resin mineral
- Electricity supply 220 V/50 Hz
- Salt Consumption 0.2kg/l/reg

### Advantages

- Easy to operate without any need full time operator
- Low operating cost
- Low energy cost

### Technical Features

CODE	MODEL	CONNECTION inc	MAX.Flow m3/h	CAPACITY m3F	MEDIA Resin lt	TANK inc	SALT TANK		TOTAL kg
							Volume lt	Dimension cm	
MM.ATF20.1	TF 20-1	1	1.2	120	20	8X35	100	50x78	47
MM.ATF30.1	TF 30-1	1	2.0	180	30	10X35	100	50x78	59
MM.ATF50.1	TF 50-1	1	2.0	300	50	10X54	100	50x78	82
MM.ATF70.1	TF 70-1	1	3.6	420	70	13X54	250	54x110	113
MM.ATF100.114	TF 100-1 1/4	1 1/4	4.0	600	100	14X65	250	54x110	156
MM.ATF125.114	TF 125-1 1/4	1 1/4	5.2	750	125	16X65	250	54x110	190
MM.ATF150.114	TF 150-1 1/4	1 1/4	6.4	900	150	18X65	500	79x114	232
MM.ATF200.2	TF 200-2	2	8.8	1200	200	21X62	500	79x114	285
MM.ATF300.2	TF 300-2	2	11.7	1800	300	24X72	500	79x114	159
MM.ATF400.2	TF 400-2	2	18.0	2400	400	30X72	750	91x98	190
MM.ATF500.2	TF 500-2	2	18.0	3000	500	30X72	750	91x98	235
MM.ATF600.2	TF 600-2	2	18.0	3600	600	36X72	750	91x98	288