

TFD AUTOTROL

SERIES DUPLEX SOFTENING SYSTEMS



Standard Features

- Corrosion resistant FRP (Fiber wound) body
- Programmable automatic FLECK valf
- Flow controlled
- Automatic backwash time setter
- 3-6 Bar operating pressure
- Max. 10 bar test pressure
- Max. 50 C operating temperature
- Food grade resin mineral
- Electricity supply 220 V/50 Hz
- Salt Consumption 0.2kg/l/reg

Advantages

- Easy to operate without any need full time operator
- Low operating cost
- Low energy cost

Technical Features

CODE	MODEL	CONNECTION inc	MAX.Flow m3/h	CAPACITY m3F	MEDIA Resin lt	TANK inc	SALT TANK		TOTAL kg
							Volume lt	Dimension cm	
MM.ATFD20.1	TFD 20-1	1	1.2	120	20X2	8X35	100	50x78	77
MM.ATFD30.1	TFD 30-1	1	2.0	180	30X2	10X35	100	50x78	101
MM.ATFD50.1	TFD 50-1	1	2.0	300	50X2	10X54	100	50x78	147
MM.ATFD70.1	TFD 70-1	1	3.6	420	70X2	13X54	250	54x110	204
MM.ATFD100.114	TFD 100-1 1/4	1 1/4	4.0	600	100X2	14X65	250	54x110	301
MM.ATFD125.114	TFD 125-1 1/4	1 1/4	5.2	750	125X2	16X65	250	54x110	363
MM.ATFD150.114	TFD 150-1 1/4	1 1/4	6.4	900	150X2	18X65	500	79x114	454
MM.ATFD200.2	TFD 200-2	2	8.8	1200	200X2	21X62	500	79x114	560
MM.ATFD300.2	TFD 300-2	2	11.7	1800	300X2	24X72	500	79x114	836
MM.ATFD400.2	TFD 400-2	2	18.0	2400	400X2	30X72	750	91x98	1168
MM.ATFD500.2	TFD 500-2	2	18.0	3000	500X2	30X72	750	91x98	1368
MM.ATFD600.2	TFD 600-2	2	20	3600	600X2	36X72	750	91x98	1677