

# FQB FLECK

## SERIES SAND IRON SYSTEMS



### Standard Features

- Corrosion resistant FRP (Fiber wounded) body
- Programmable automatic FLECK valf
- Automatic backwash time setter
- 3-6 Bar operating perssure
- Max. 10 bar test pressure
- Max. 50 C operating temperature
- Birm and 3 different granule size mineral content
- Electricity supply 220 V/50 Hz

### Advantages

- Easy to operate without any need full time operator
- Low operating cost
- Low energy cost



### Technical Features

CODE	MODEL	CONNECTION inc	FLOW m3/h		BACK WASH 35 m/h	TANK inc	TANK m2	MEDIA			TOTAL kg
			15 m/h	20 m/h				Antrachyte kg	Birm kg	Gravel kg	
MM.YFQB20.1	FQB 20-1	3/4 - 1	0.45	0.6	1.1	8X35	0.03	5	7	5	33
MM.YFQB30.1	FQB 30-1	3/4 - 1	0.75	1.0	1.8	10X35	0.05	7	15	7	45
MM.YFQB50.1	FQB 50-1	3/4 - 1	0.75	1.0	1.8	10X54	0.05	10	20	7	56
MM.YFQB70.1	FQB 70-1	1	1.35	1.8	3.2	13X54	0.09	15	25	25	90
MM.YFQB100.1	FQB 100-1	1	1.5	2.0	3.5	14X65	0.10	25	37	25	120
MM.YFQB125.1	FQB 125-1	1	1.95	2.6	4.6	16X65	0.13	25	50	25	134
MM.YFQB150.15	FQB 150-1 1/2	1 1/2	2.4	3.2	5.6	18X65	0.16	50	75	50	224
MM.YFQB200.15	FQB 200-1 1/2	1 1/2	3.3	4.4	7.7	21X62	0.22	50	100	50	252
MM.YFQB250.2	FQB 250-2	2	4.35	5.8	10.2	24X72	0.29	50	125	50	339
MM.YFQB400.2	FQB 400-2	2	6.75	9.0	15.8	30X72	0.45	150	200	200	676
MM.YFQB600.2	FQB 600-2	2	10	13.2	23.1	36X72	0.66	200	300	300	958
MM.YFQB750.2	FQB 750-2	2	13.4	17.8	31.2	42X72	0.89	225	350	350	1175