

CARTRIDGE FILTERS 2

Standard Features

- Filtration for desired microns
- 2-7 bar operating pressure
- 2-45 C operating temperature

Nylon Cartridges

CODE	MODEL	MICRON	FLOW m ³ /h
MM.KRTCX.10	CN10	50	3
MM.KRTCX.20	CN20	50	6
MM.KRTCX.30	CN30	50	9
MM.KRTCX.40	CN40	50	12



Stainless Steel Cartridges

CODE	MODEL	MICRON	FLOW m ³ /h
MM.KRTCX.10	CX10	50	3
MM.KRTCX.20	CX20	50	6
MM.KRTCX.30	CX30	50	9
MM.KRTCX.40	CX40	50	12



Block Carbon Cartridges

CODE	MODEL	MICRON	FLOW m ³ /h
MM.KRTGAC.10	10" GAC	5	0.3
MM.KRTAKC.20	20" BLOK	5	2



Big Blue Cartridges

CODE	MODEL	MICRON	FLOW m ³ /h
MM.KRTBIGCP.10	PP 10"	5	5
MM.KRTBIGCP.20	PP 20"	5	10
MM.KRTBIGNYL.10	NAYLON 10"	50	10
MM.KRTBIGNYL.20	NAYLON 20"	50	20
MM.KRTBIGAC.10	KARBON 10"	5	5
MM.KRTBIGAC.20	KARBON 20"	5	10

