

# UVC MONO

ULTRAVIOLET SYSTEMS



## Standard Features

- 304 Stainless Steel Body
- Mirror polished surface
- IP54 Control Panel
- Electronic Card
- High Quality quartz Sleeve
- Timer
- 9000 Hours lamp life
- Electricity Supply 220-230 V / 50-60 Hz
- 2-7 bar operating temperature
- 2-45 C operating temperature

## Optional Features

- 316 Stainless Steel Body
- 16 bar resistant design
- Beam sensor monitor

## Design Criterias

- Temperature 20 C
- Clear appearance
- Fe < 0,2 mg/l
- Mn < 0,05 mg/l
- TDS < 10 mg/l
- Transmission rate % 95

## Technical Features

CODE	MODEL	FLOW m3/h 30,000uW/cm2	FLOW m3/h 40,000uW/cm2	CONNECTION inc	LAMP Qty.	LAMP Watt	BODY mm	PANEL mm	WEIGHT kg
MM.UVC12.304	UVC 12 S	0.26	0.2	1/4	1	12	60x205	ADAPTÖRLÜ	1.25
MM.UVC30.304	UVC 30 S	1.5	1.2	3/4	1	30	60x450	200x155x80	2.5
MM.UVC40.304	UVC 40 S	2.8	2.4	1	1	40	60x870	200x155x80	5.5
MM.UVC65.304	UVC 65 S	5	4	1 1/4	1	65	60x870	200x155x80	5.5