

# UVC MULTI

## ULTRAVIOLET SYSTEMS



### Standard Features

- 304 Stainless Steel Body
- Mirror polished surface
- IP54 Control Panel
- Electronic Card for each lamp
- High Quality quartz Sleeve for each lamp
- Timer
- 9000 Hours lamp life
- Electricity Supply 220-230 V / 50-60 Hz
- 2-7 bar operating temperature
- 2-45 C operating temperature

### Optional Features

- 316 Stainless Steel Body
- 16 bar resistant design
- Beam sensor monitor
- Flanged connection

### Design Criterias

- Temperature 20 C
- Clear appearance
- Fe < 0,2 mg/l
- Mn < 0,05 mg/l
- TDS < 10 mg/l
- Transmission rate % 95



### Technical Features

CODE	MODEL	FLOW m <sup>3</sup> /h 30,000uW/cm <sup>2</sup>	FLOW m <sup>3</sup> /h 40,000uW/cm <sup>2</sup>	CONNECTION inc	LAMP Qty.	LAMP Watt	BODY mm	PANEL mm	WEIGHT kg
MM.UVC80.304	UVC 80 S	6	4.6	1 1/2	2	80	114x885	320x240x135	12.5
MM.UVC120.304	UVC 120 S	9	7	2	3	120	114x885	320x240x135	13
MM.UVC160.304	UVC 160 S	12	9	2	4	160	140x885	300x400x165	19
MM.UVC240.304	UVC 240 S	20	15	3	6	240	219x850	400x500x175	40
MM.UVC320.304	UVC 320 S	25	20	3	8	320	219x850	400x500x175	40
MM.UVC390.304	UVC 390 S	33	25	3	6	390	219x850	400x500x175	40
MM.UVC520.304	UVC 520 S	43	33	3	8	520	219x850	400x500x175	40
MM.UVC780.304	UVC 780 S	65	50	4	12	780	273x895	700x500x245	60
MM.UVC1040.304	UVC 1040 S	86	65	4	16	1.040	324x895	845x500x240	96