

# TFV FLECK

## SERIES SOFTENING SYSTEMS



### Standard Features

- Corrosion resistant FRP (Fiber wound) body
- Protection cover on top salt tank
- Programmable automatic FLECK valf
- Flow controlled
- Automatic backwash time setler
- 3-6 Bar operating perssure
- Max. 10 bar test pressure
- Max. 50 C operating temperature
- Food grade resin mineral
- Electricity supply 220 V/50 Hz
- Salt Consumption 0.2kg/lt/reg

### Advantages

- Easy to operate without any need full time operator
- Low operating cost
- Low energy cost

### Technical Features

CODE	MODEL	CONNECTION inc	MAX.Flow m3/h	CAPACITY m3F	MEDIA		TANK inc	SALT TANK		TOTAL kg
					Resin Lt	Gravel kg		Volume Lt	Dimensions cm	
MM.YTF20.1V	TF 20-1	3/4 -1	1.2	120	20	3	8X35	100	50x78	47
MM.YTF30.1V	TF 30-1	3/4 -1	2.0	180	30	5	10X35	100	50x78	59
MM.YTF50.1V	TF 50-1	1	2.0	300	50	5	10X54	100	50x78	82
MM.YTF70.1V	TF 70-1	1	3.6	420	70	10	13X54	100	50x78	113
MM.YTF100.1V	TF 100-1	1	4.0	600	100	15	14X65	100	50x78	156
MM.YTF125.1V	TF 125-1	1	5.0	750	125	20	16X65	250	54x110	190
MM.YTF150.1V	TF 150-1	1	5.0	900	150	25	18X65	250	54x110	232
MM.YTF200.1V	TF 200-1	1	5.0	1.200	200	25	21X62	250	54x110	285
MM.YTF100.15V	TF 100-1 1/2	1 1/2	4.1	600	100	15	14X65	100	50x78	159
MM.YTF125.15V	TF 125-1 1/2	1 1/2	5.2	750	125	20	16X65	100	50x78	190
MM.YTF150.15V	TF 150-1 1/2	1 1/2	6.4	900	150	25	18X65	250	54x110	235
MM.YTF200.15V	TF 200-1 1/2	1 1/2	8.8	1.200	200	25	21X62	250	54x110	288
MM.YTF300.15V	TF 300-1 1/2	1 1/2	10.0	1.800	300	50	24X72	500	79x114	439
MM.YTF200.2V	TF 200-2	2	8.8	1.200	200	25	21X62	250	54x110	306
MM.YTF300.2V	TF 300-2	2	11.7	1.800	300	50	24X72	500	79x114	457
MM.YTF400.2V	TF 400-2	2	18.0	2.400	400	75	30X72	500	79x114	619
MM.YTF500.2V	TF 500-2	2	18.0	3.000	500	75	30X72	500	79x114	719
MM.YTF600.2V	TF 600-2	2	20.0	3.600	600	100	36X72	750	91x98	882
MM.YTF850.2V	TF 850-2	2	20.0	5.100	850	150	42X72	750	91x98	1.274
MM.YTF600.3V	TF 600-3	3	26.3	3.600	600	100	36X72	750	91x98	917
MM.YTF850.3V	TF 850-3	3	36.0	5.100	850	150	42X72	1.000	199x107	1.313
MM.YTF1100.3V	TF 1100-3	3	46.0	6.600	1.100	250	48X72	1.500	128x130	1.704