

FQ AUTOTROL

SERIES MULTI MEDIA SYSTEMS



Standard Features

- Corrosion resistant FRP (Fiber wounded) body
- Programmable automatic AUTOTROL valf
- Automatic backwash time setter
- 3-6 Bar operating perssure
- Max. 10 bar test pressure
- Max. 50 C operating temperature
- 4 different granule size mineral content
- Electricity supply 220 V/50 Hz

Advantages

- Easy to operate without any need full time operator
- Low operating cost
- Low energy cost

Technical Features

CODE	MODEL	CONNECTION inc	FLOW m ³ /h		BACK WASH 35 m/h	TANK inc	TANK m ²	MEDIA			TOTAL kg
			20 m/h	30 m/h				Antrachyte kg	Sand kg	Gravel kg	
MM.AFQ20.1T	FQ 20-1	1	0.6	0.9	1.1	8X35	0.03	5	7	5	33
MM.AFQ30.1T	FQ 30-1	1	1.0	1.5	1.8	10X35	0.05	7	15	7	45
MM.AFQ50.1T	FQ 50-1	1	1.0	1.5	1.8	10X54	0.05	10	20	7	56
MM.AFQ70.11/4T	FQ 70-1 1/4	1 1/4	1.8	2.7	3.2	13X54	0.09	15	25	25	90
MM.AFQ100.11/4T	FQ 100-1 1/4	1 1/4	2.0	3.0	3.5	14X65	0.10	25	37	25	120
MM.AFQ125.11/4T	FQ 125-1 1/4	1 1/4	2.6	3.9	4.6	16X65	0.13	25	50	25	134
MM.AFQ150.11/4T	FQ 150-1 1/4	1 1/4	3.2	4.8	5.6	18X65	0.16	50	75	50	224
MM.AFQ150.2T	FQ 150-2	2	3.2	4.8	5.6	18X65	0.16	50	75	50	224
MM.AFQ200.2T	FQ 200-2	2	4.4	6.6	7.7	21X62	0.22	50	100	50	252
MM.AFQ250.2T	FQ 250-2	2	5.8	8.7	10.2	24X72	0.29	50	125	50	339
MM.AFQ400.2T	FQ 400-2	2	9.0	13.5	15.8	30X72	0.45	150	200	200	676
MM.AFQ600.2T	FQ 600-2	2	13.2	19.8	23.1	36X72	0.66	200	300	300	958